

SUNCOAT GLOSS COATING 6244

Waterbased gloss overprint varnish

Characteristics

SUNCOAT 6244 PROVIDES A GOOD GLOSS AND RELATIVELY FAST DRYING AND GOOD WET BLOCKING RESISTANCE, GOOD STACKING CHARACTERISTICS

Standard product

SUNCOAT 6244 45 sec.

Properties of SUNCOAT 6244

- GOOD GLOSS (depending on substrate)
- Relatively fast drying
- Fair wet blocking resistance and good stacking characteristics
- Very good rub resistance
- Good hot-sealing resistance
- No yellowing (depending on substrate)
- Suitable for carton
- Low odour during application, odour free dried film, well suitable for food packaging (indirect contact)
- Good glueability by dispersion glues (product oriented test necessary), fairly glueable by hot melt (product oriented test necessary)

Marking

No hazardous substance or preparation according to EEC-Directives 67/548/EEC or 1999/45/EEC. The safety data sheet is available on request.

Packaging size

SUNCOAT is available in 25 kg and 200 kg one-way containers or in 600 kg and 1000 kg multi-use containers. On request we can offer a drain cock for the multi-use containers.

General Information

Products should be stirred before using.

Protect product against frost. Frozen products should be warmed up slowly and carefully (no heating) and stirred well prior to application.

Care should be taken when coated inks containing sensitive pigments with poor resistance to ammonia and alcohol (solvents). Please ensure appropriate ink fastness.

Guaranteed shelf-life 6 months after dispatch