



TARJETA DE ESPECIFICACIONES

Fecha de Expedicion: 19.10.2015

Descripción del Material: 1300073 / Cartulina Esmaltada Corriente 30

CARACTERISTICA	METODO	UN	ESPECIFICACION		
			ESTANDAR	MINIMO	MAXIMO
PESO BASICO	T410	g/m2	260.0	247.0	273.0
HUMEDAD	T412	%	7.5	6.0	8.5
U BLOCK	1CC0408	LB	100.0	95.0	110.0
RIGIDEZ CD	T822	LB	65.0	60.0	90.0
CALIBRE	T411	mm/100	31.0	30.0	33.0
APRESTO CREMA (SEG)	T432	s	60.0	20.0	100.0
RIGIDEZ MD	T822	LB	90.0	80.0	110.0
RIGIDEZ TABER MD	T489	gcm	85.0	78.0	90.0
RIGIDEZ TABER CD	T489	gcm	30.0	26.0	40.0
BLANCURA	T452	%	73.0	72.0	75.0
LISURA	T538	US	80.0	70.0	100.0
DOBLEZ (AL 6.5%)	VISUAL				
IGT	T514	cm/s	115.0	103.0	125.0
INTERNAL BOND	T569	Jul/m2	180.0	170.0	240.0

Documento: 1-CC-10-01

Fecha Ultima modificacion: 19.10.2015

Generate by SAP